



SOLVENT—BASED PRIMER PRODUCT SUITE - LINE CARD

PRODUCT	DESCRIPTION	COATING METHOD	BASE	SUBSTRATE	CURE	FEATURES
CrystalCoat™ Glass Primer	Air or dry or thermal cure primer designed to provide an adhesion layer for application to glass substrates	Dip, Spin, Spray	Solvent	Glass	Air or dry or thermal cure	1% solids, air or thermal cure primer designed to provide an adhesion layer for application to glass substrates.
CrystalCoat PR-1165	Imparts adhesion to PC. Ideally suited to applications where fast air dry is required. Pretreatment recommended on PC, REACH compliant.	Dip, Spin	Solvent	Acrylic, CR-39®, RAV 7®, Nylon, Polycarbonate	Room temperature at 15 minutes. Infrared or convection heater at <5 minutes	Rapid air dry, improves impact resistance.
CrystalCoat UV P-201B	UV curable primer for ophthalmic lenses or other plastic parts.	Flow, Spin, Spray	Solvent	Designed for ADC (CR- 39®, RAV 7®), Trivex®, Mid-Index Acrylic	UV Cure	Designed to provide an adhesion layer for application to CR- 39® and Mid-index substrates.
CrystalCoat UV P-201C	UV curable primer for ophthalmic lenses or other plastic parts.	Flow, Spin, Spray	Solvent	Acrylic (PMMA) Polycarbonate	UV	Designed to provide an adhesion layer for application to polycarbonate and PMMA substrates.

© 2020 All Rights Reserved. SDC Technologies, Inc. is a subsidiary of Mitsui Chemicals, Inc. CrystalCoat[™] is a trademark of SDC Technologies. RAV 7[®] is a registered trademark of Acomon AG. Acomon AG is a subsidiary of Mitsui Chemicals, Inc. CR-39[®] is a registered trademark of PPG.

